

Dübelgrösse		4	5	6	8	10	12	14	16	20	
Empfohlene Zuglasten ¹⁾ :											
N _{Emp}	- Beton	0.25	0.35	0.6	0.85	1.4	1.8	3	3.5	5.2	
	- Vollziegel	0.2	0.3	0.5	0.8	1	1.4	1.5	-	-	
	- Leichtbeton	0.02	0.04	0.06	0.09	0.2	0.4	0.5	0.6	1	
Für Schraubenabmessung:											
d _s	- Holzschrauben-Ø	mm	2.2-3	2.6-4	3.5-5	4.5-6	6-8	8-10	10-12	12-14	14-16
	- Spanplattenschrauben-Ø	mm	2.2-3	2.6-4	3.5-5	4.5-6	6-8	8-10	10-12	12-14	14-16
	- Metrische Schraube	M	-	3	4	5	6	8	10	12	14
h ₁	Bohrlochtiefe	mm	30	35	40	55	65	80	90	100	115
d ₀	Bohrloch-Ø im Baustoff	mm	4	5	6	8	10	12	14	16	20
l	Dübellänge	mm	20	25	30	40	50	60	70	80	90
d _{nom}	Dübel-Ø	mm	4	5	6	8	10	12	14	16	20



- 1) Holzschrauben mit maximal möglichem Durchmesser / Sicherheitsfaktor 5
 2) Distanzmontage in Kombination mit Distanzschraube